

Jump Ring Aspect Ratios - Round Wire - Standard Wire Gauge (SWG)

Wire Diameter			0.028"	0.032"	0.036"	0.04"	0.048"	0.064"	0.08"	0.104"
			0.711mm	0.813mm	0.914mm	1.016mm	1.219mm	1.626mm	2.032mm	2.642mm
ID inches	ID inches	ID mm	22 gauge	21 gauge	20 gauge	19 gauge	18 gauge	16 gauge	14 gauge	12 gauge
	0.078	2.0	2.8	2.4	2.2	2.0	1.6			
3/32	0.094	2.4	3.3	2.9	2.6	2.3	2.0			
		2.5	3.5	3.1	2.7	2.5	2.1			
7/64	0.109	2.8	3.9	3.4	3.0	2.7	2.3	1.7		
		3.0	4.2	3.7	3.3	3.0	2.5	1.8		
1/8	0.125	3.2	4.5	3.9	3.5	3.1	2.6	2.0	1.6	
		3.5	4.9	4.3	3.8	3.4	2.9	2.2	1.7	
9/64	0.141	3.6	5.0	4.4	3.9	3.5	2.9	2.2	1.8	
5/32	0.156	4.0	5.6	4.9	4.3	3.9	3.3	2.4	2.0	
		4.2	5.9	5.1	4.6	4.1	3.4	2.6	2.1	
11/64	0.172	4.4	6.1	5.4	4.8	4.3	3.6	2.7	2.1	1.7
		4.5	6.3	5.5	4.9	4.4	3.7	2.8	2.2	1.7
3/16	0.188	4.8	6.7	5.9	5.2	4.7	3.9	2.9	2.3	1.8
		5.0	7.0	6.2	5.5	4.9	4.1	3.1	2.5	1.9
13/64	0.203	5.2	7.3	6.3	5.6	5.1	4.2	3.2	2.5	2.0
		5.5	7.7	6.8	6.0	5.4	4.5	3.4	2.7	2.1
7/32	0.219	5.6	7.8	6.8	6.1	5.5	4.6	3.4	2.7	2.1
15/64	0.234	6.0	8.4	7.3	6.5	5.9	4.9	3.7	2.9	2.3
1/4	0.250	6.4	8.9	7.8	6.9	6.3	5.2	3.9	3.1	2.4
		6.5	9.1	8.0	7.1	6.4	5.3	4.0	3.2	2.5
		7.0	9.8	8.6	7.7	6.9	5.7	4.3	3.4	2.6
9/32	0.281	7.1	10.0	8.8	7.8	7.0	5.9	4.4	3.5	2.7
		7.5	10.5	9.2	8.2	7.4	6.2	4.6	3.7	2.8
5/16	0.313	7.9	11.2	9.8	8.7	7.8	6.5	4.9	3.9	3.0
		8.0	11.2	9.8	8.7	7.9	6.6	4.9	3.9	3.0
		8.5	12.0	10.5	9.3	8.4	7.0	5.2	4.2	3.2
11/32	0.344	8.7	12.3	10.7	9.5	8.6	7.2	5.4	4.3	3.3
		9.0	12.7	11.1	9.8	8.9	7.4	5.5	4.4	3.4
3/8	0.375	9.5	13.4	11.7	10.4	9.4	7.8	5.9	4.7	3.6
		10.0	14.1	12.3	10.9	9.8	8.2	6.2	4.9	3.8
13/32	0.406	10.3	14.5	12.7	11.3	10.2	8.5	6.3	5.1	3.9
		11.0	15.5	13.5	12.0	10.8	9.0	6.8	5.4	4.2

7/16	0.438	11.1	15.6	13.7	12.2	10.9	9.1	6.8	5.5	4.2
15/32	0.469	11.9	16.7	14.6	13.0	11.7	9.8	7.3	5.9	4.5
		12.0	16.9	14.8	13.1	11.8	9.8	7.4	5.9	4.5
1/2	0.500	12.7	17.9	15.6	13.9	12.5	10.4	7.8	6.3	4.8